

KENWOOD

Listen to the Future



TK-690/790/890

VHF/UHF FM Mobile Radios

FleetSync[®]
by KENWOOD

GENERAL FEATURES

- 45W & 110W (136-156, 148-174 MHz)
- 40W (403-430, 450-490, 480-512 MHz)
- 110W-75W (450-480 MHz)
- 110W (29.7-37.0, 35.0-43.0, 40.0-50.0 MHz)
- 160 Channels
- Dual Priority Scan
- Single / Multi Group Scan
- QT / DQT
- Operator Selectable Tone
- Two-Tone Decode¹
- DTMF Encode/ Decode / Stun²
- Encryption / ANI Board Control³
- Emergency Call Features
- Companded Audio
- Intercom⁴
- Public Address
- Time Out Timer
- Busy Channel Lockout
- Ignition Sense⁵
- Timed Power Off
- DB-25 Accessory Connector⁶
- 7 Programmable AUX Inputs⁶

- 6 Programmable AUX Outputs⁶
- Windows[®] Programming & Tuning⁷
- Windows[®] Firmware Uploading⁷
- Panel Tuning
- Cloning
- MIL-STD-810 C/D/E/F
- MIL-Spec Noise-Cancel Mic (included)
- MIL-Spec 12-Key DTMF Mic Option

FleetSync[®]

- PTT ID Digital ANI
- Emergency Status

MOUNTING CONFIGURATIONS

- Dash Mount
- Single Head Remote Mount
- Dual Head Remote Mount
- Dual Band Remote Mount
- Dual Head / Dual Band Remote Mount

FRONT PANELS / CONTROL HEADS

- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function/Status LCD Icons

- Transmit LED
- Busy, Call Alert, Warn LED
- LCD Dimmer Control
- Power On/Off Switch
- Rotary Volume Knob
- Rotary Selector Knob
- Backlit Keys
- PF Key Label Inserts
- Microphone Jack
- MILSTD 810 512.X Driven Rain

KCH-10 FRONT PANEL

- 8-Character Alphanumeric Aliases
- 5 PF Keys
- UP/DOWN Keys
- Built-in Front Speaker

KCH-11 FRONT PANEL

- 14-Character Alphanumeric Aliases
- 13 PF Keys
- UP/DOWN Keys
- External Speaker Required



Options

- KMC-9B**
Desktop Microphone
- KMC-27**
Microphone
(MIL-SPEC noise-canceling)
- KMC-28**
Keypad Microphone
(MIL-SPEC noise-canceling)
- KCT-18**
Ignition Sense Cable
- KCT-22**
Remote Control Cable
- KCT-23**
DC Power Cable
- KES-5**
External Speaker (20W)
- KCH-10**
Basic Remote
Control Head
- KCH-11**
Full-Featured Remote
Control Head
- KRK-5**
Single Control Head Remote Kit
- KRK-6DH**
Dual Control Head Remote Kit
- KRK-7DB**
Dual Band Remote Kit
- KRK-8DBH**
Dual Band & Dual Control Head Remote Kit

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-690H	TK-790H	TK-790	TK-890H	TK-890
GENERAL					
Frequency Range					
Type 1	29.7-37.0 MHz	148-174 MHz	148-174 MHz	450-480 MHz	450-490 MHz
Type 2	35.0-43.0 MHz		136-156 MHz		480-512 MHz
Type 3	40.0-50.0 MHz				403-430 MHz
Number of Channels	160				
Channel Spacing					
Wide	20 kHz	25, 30 kHz	25, 30 kHz	25 kHz	25 kHz
Narrow		12.5, 15 kHz	12.5, 15 kHz	12.5 kHz	12.5 kHz
Channel Step	5 kHz	2.5 / 5 / 6.25 / 7.5 kHz	2.5 / 5 / 6.25 / 7.5 kHz	5 / 6.25 kHz	5 / 6.25 kHz
Operating Voltage	13.4 V DC ±15%	13.4 V DC ±15%	13.6 V DC ±15%	13.4 V DC ±15%	13.6 V DC ±15%
Current Drain					
Standby	< 0.6 A	< 0.6 A	< 0.6 A	< 0.6 A	< 0.6 A
Receive	< 2.2 A	< 2.2 A	< 2.2 A	< 2.2 A	< 2.2 A
Transmit	< 25 A	< 25 A	< 12 A	< 28 A	< 12 A
Duty Cycle	Transmit: 20%				
Operating Temperature Range	-22°F ~ +140°F (-30°C ~ +60°C)				
Frequency Stability (-22° F - +140° F)	±0.0005%	±0.0002%	±0.0002%	±0.0002%	±0.0002%
Antenna Impedance	50 Ω				
Dimensions (W x H x D) (w/ KCH-10)	7x2-1/4x14 1/8in. (178x60x360 mm)	7x2-1/4x14 1/8in. (178x60x360 mm)	7x2-1/4x9 in. (178x60x228 mm)	7x2-1/4x14 1/8in. (178x60x360 mm)	7x2-1/4x9 in. (178x60x228 mm)
Weight (net)	7.9 lbs. (3.6kg)	7.9 lbs. (3.6kg)	5 lbs. (2.3kg)	7.9 lbs. (3.6kg)	5 lbs. (2.3kg)
FCC ID					
Type 1	ALH22923110	ALH22933210	ALH22933110	ALH22943210	ALH22943110
Type 2	ALH22923120		ALH22933120		ALH22943120
Type 3	ALH22923130				ALH22943130
IC Certification					
Type 1	282195519A	282195450A	282195451A	282195446A	282195447A
Type 2	282195532A		282195510A		
Type 3	282195520A				
RECEIVER (Measurements made per EIA/TIA-204-D)					
Sensitivity (12dB SINAD) (20dB Quieting)	0.25µV 0.35µV	0.25µV 0.35µV	0.25µV 0.35µV	0.25µV 0.35µV	0.25µV 0.35µV
Selectivity					
Wide	85 dB	85 dB	85 dB	85 dB	85 dB
Narrow		80 dB	80 dB	77 dB	77 dB
Intermodulation Distortion					
Wide	80 dB	80 dB	80 dB	80 dB	80 dB
Narrow		75 dB	75 dB	75 dB	75 dB
Spurious Response	90 dB	90 dB	90 dB	90 dB	90 dB
Audio Output	13W at 4Ω with less than 5% distortion (12W 4Ω with less than 3% distortion)				
TRANSMITTER (Measurements made per EIA/TIA-152-C)					
RF Output Power	110-45 W	110-45 W	45-5 W	100-40 W (75-40W in 470-480 MHz)	40-5 W
Type of Emission					
Wide	16K0F3E	16K0F3E	16K0F3E	16K0F3E	16K0F3E
Narrow		11K0F3E	11K0F3E	11K0F3E	11K0F3E
Spurious Response	80 dB	80 dB	80 dB	80 dB	80 dB
FM Hum & Noise					
Wide	55dB	53dB	53dB	50dB	50dB
Narrow		47dB	47dB	44dB	44dB
Microphone Impedance	600 Ω				
Audio Distortion	Less than 2% at 1000 Hz				

Kenwood follows a policy of continuous advancement in development. For this reason specifications may be changed without notice.

FleetSync® is a registered trademark of Kenwood Corporation.
LTR® is a registered trademark of Transcript International.
All other trademarks are property of their respective owners.

Applicable MIL-STD

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I*, II	506.2/Procedure I*, II	506.3/Procedure I*, II	506.4/Procedure I*, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV

* Control head only

footnotes from Front:

- ¹ Two-Tone Decode (3 sets x 2 pairs each), Operator Selectable Tone (16 QT.DQT code pairs)
- ² DTMF Encode: PTT ID, Emergency ANI, Manual Encode (KMC-28), Auto-Dial (9 numbers); DTMF Decode: Primary/Secondary ID, Stun (a.k.a. dead beat disable)
- ³ Encryption/ANI Board: PCB lands for wire harness connectors. Intercom: Dual Head & Dual Head/Dual Band remote mounts only
- ⁴ DB-25 ACC: I/O's for dispatch consoles, desktop remotes, vehicle intercom/PA units, motorcycle PTT/headset kits, PC Laptop /Data Modems, GPS/AVL Modems.
- ⁵ KCT-18 Ignition sense option required.
- ⁶ DB-25 ACC: I/O's for dispatch consoles, desktop remotes, vehicle intercom/PA units, motorcycle PTT/headset kits, PC Laptop /Data Modems, GPS/AVL Modems.
- ⁷ KPG-44D Software required (Windows*98/NT/2000/Me/XP compatible)

KENWOOD

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8



ISO9001 Registered
Communications Equipment Division
Kenwood Corporation
ISO9001 certification